



 **Sealed Air**

NewAir I.B.® Express

Inflatable Cushioning System

 **SYNERGY**
packaging•solutions

The versatile, inflatable cushioning system for any packaging operation



The NewAir I.B.[®] Express System

Patented technology ensures fast, reliable inflatable cushioning

The difference is in the Barrier Bubble[®] technology

The NewAir I.B.[®] Express packaging system automatically inflates and dispenses patented Barrier Bubble[®] cushioning material. The Sealed Air proprietary film technology retains air longer than non-barrier polyethylene air cellular materials and out-performs other materials for cushioning and overall packaging protection.



Unmatched cushioning properties

Designed to withstand the rigors of today's global shipping environments, NewAir I.B.[®] inflatable cushioning material maintains its excellent cushioning properties throughout the entire shipping cycle.

Tiny footprint, enormous production

The NewAir I.B.[®] Express inflatable cushioning system from Sealed Air quickly produces inflatable cushioning, in 300mm and 600mm film widths, at speeds up to 20 metres per minute – fast enough to keep up with the most demanding packaging operations. The small footprint and variety of batching, delivery and converting options make the NewAir I.B.[®] Express system the perfect fit in almost any packaging environment.



The right material for your application

With the NewAir I.B.[®] Express system, you can customise the cushioning output. Choose between two different film widths, 300mm and 600mm, and a variety of regular and premium film options.*



* Pre-Inflated film widths 400mm and 800mm, Inflated film widths 300mm and 600mm.

Save valuable floor space

The NewAir I.B.[®] Express has a compact footprint (less than 0.6m²) that works well in cellular packaging environments. The compact design fits comfortably on a tabletop, or can be mounted on a table-side stand. A single film roll can equal 456m² of extra large bubble material, creating on-demand packaging that saves storage space and handling.



System accessories for every configuration

The NewAir I.B.[®] Express is supported by a large array of system accessories, making it flexible enough to be used in any and every packaging operation.

SystemStand and Roll Winder

With the optional Roll Winder attachment, the NewAir I.B.[®] Express system can create a 900mm roll of material in under three minutes, for decentralised packaging environments.




Instasheeter[™] converting system

At the touch of a footswitch, the Instasheeter[™] converting system cuts custom sheets of NewAir I.B.[®] material that provide excellent cushioning or blocking and bracing.



Specifications

Electrical:
220/240 VAC 50 Hz
2 A, Single Phase
Weight (without roll):
36.7 kg.
Overall Size (L x W x H):
77cm x 67cm x 46cm
With standard width roll



 **Sealed Air**

 **SYNERGY**
packaging•solutions

0800 228 9883

www.synergypackaging.co.uk

Sealed Air has companies throughout the world.
© Sealed Air Corporation 2010. All rights reserved.

